

## NATIONAL INSTITUTE OF TECHNOLOGY TIRUCHIRAPPALLI – 620 015 ESTATE MAINTENANCE DEPARTMENT

## NOTICE INVITING TENDERS TENDER NOTIFICATION

Ref: NITT/EO/EMD/Civil Works/ En. No. 42/2015 -16

The **Estate Officer**, **E**state **M**aintenance **D**epartment, **NIT-T**richy - 620 015 invites on behalf of The Director, NIT-Trichy - 620 015 sealed item rate tenders from the approved and eligible contractors of NITT/CPWD and those in the appropriate list of Tamil Nadu state PWD, Railways, MES and BSNL for the following work. Sealed tenders will be received by the Registrar, National Institute of Technology, Tiruchirappalli-15 up to **3.00 p.m. on 15.02.2016**. The tender will be **opened at 3.30 p.m.** on **15.02.2016** at **R**egistrar **O**ffice, in the presence of tenders who choose to present.

En.No	Est. Id No	Name of work	Estimate Cost Rs.	E.M.D Rs.	Last Date for submission of tenders	Tender cost
42	109	Removing and re-fixing the existing paver block flooring in path way of opal hostel premises.	3,00,770/-	6,100/-	15.02.2016	Rs.150/-

Tender details in this regard may also be seen in the Notice board of office of the Estate office, Estate Maintenance Department, NIT, Trichy -15 during office hours on any working days.

The tender document can be downloaded from the Institute Web Site <a href="https://www.nitt.edu/home/others/tenders/">www.nitt.edu/home/others/tenders/</a>. The tender cost and Earnest money should be enclosed along with tender schedule in the form of separate **D**emand **D**raft of any Nationalized bank Drawn in favour of "The **Director, NIT,Trichy – 15.** 

-Sd-Estate Officer

Date: 29.01.2016

## NAIONAL INSTITUTE OF TECHNOLOGY, TIRUCHIRAPPALLI - 620015 DEPARTMENT OF ESTATE MAINTRNANCE TENDER DOCUMENT

N/W: Removing and re-fixing the existing paver block flooring in path way of Opal hostel premises.

**Ref**: NITT/EMD/EO/Civil Works/En. No.42(109)/15-16, dated 29.01.2016

**Due On – 15.02.2016** 

## Name of the Agency:

ITEM No	SUB-HEADS AND ITEM OF WORK	QUANTITY	UNIT	RATE (Rs)	RATE (In Words)	AMOUNT(Rs)
1	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	8.00	Cum			
2	Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with fine sand etc. all complete as per the direction of Engineer-in-charge.	100.00	Sqm			
3	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement concrete in position to the required line, level and curvature, jointed with cement mortar 1:3 (1 cement: 3 coarse sand), including making joints with or without grooves (thickness of joints except at sharp curve shall not to more than 5mm), including making drainage opening wherever required complete etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast	2.00	Cum			

	C.C. kerb stone shall be approved by Engineer-in-charge).				
4	Taking out existing kerb stones of all types from footpath/central verge, including removal of mortar etc., disposal of unserviceable material to the dumping ground, for which payment shall be made separately and stacking of serviceable material within 50 metre lead as per direction of Engineer-in-Charge.	150.00	Metre		
5	Taking out existing CC interlocking paver blocks from footpath/ central verge, including removal of rubbish etc., disposal of unserviceable material to the dumping ground, for which payment shall be made separately and stacking of serviceable material within 50 metre lead as per direction of Engineer-in-Charge.	850.00	Sqm		
6	Laying old cement cocrete interlocking paver blocks of any design/ shape laid in required line, level, curvature, colour and pattern over and including 50 mm thick compacted bed of coarse sand, filling the joints with fine sand etc. all complete as per the direction of Engineer- incharge. (Old CC paver blocks shall be supplied by the department free of cost).	850.00	Sqm		

7	Laying at or near ground level old kerb stones of all types	150.00	Metre			
	in position to the required line, level and curvature,					
	jointed with cement mortar 1:3 (1 cement : 3 coarse					
	sand), including making joints with or without grooves					
	(thickness of joints, except at sharp curve, shall not be					
	more than 5 mm), including making drainage opening					
	wherever required etc. complete as per direction of					
	Engineer-in-charge. (Length of finished kerb edging shall					
	be measured for payment). (Old kerb stones shall be					
	supplied by the department free of cost)					
	TOTAL					

SIGNATURE OF CONTRACTOR