## NATIONAL INSTITUTE OF TECHNOLOGY, TIRUCHIRAPPLLI- 620015 ESTATE MAINTENANCE DEPARTMANT

## **SCHDULE OF WORK**

Name of Work: Alumiium Partition works for SIF Lab - I

Ref: NITT/ CoW/EMD/Civil Works/ En. No.23(1)/14-15, Dt.19.12.2014

NAME OF THE CONTRACTOR / FIRM:

| ITEM No | SUB-HEADS AND ITEM OF WORK  | QTY   | UNIT | RATE (Rs) | RATE (In Words) | AMOUNT(Rs) |
|---------|---|-------|------|-----------|-----------------|------------|
| 1       | WOOD AND P. V. C. WORK  |       |      |           |                 |            |
| 1.1     | Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS: 3564, embossed on the body, door   | 8.00  | Each |           |                 |            |
|         | weight upto 36 kg to 80 kg and door width from 701 mm to 1000 mm), with double speed adjustment with necessary accessories and screws etc. complete.  |       |      |           |                 |            |
| 1.2     | Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete:                 | 17.00 | Each |           |                 |            |
| 1.3     | Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete:                     | 17.00 | Each |           |                 |            |
| 1.3.1   | 100 mm  |       |      |           |                 |            |
| 1.4     | Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete. | 8.00  | Each |           |                 |            |
| 1.4.1   | Single rubber stopper   |       |      |           |                 |            |

| ITEM No | SUB-HEADS AND ITEM OF WORK  | QTY  | UNIT | RATE (Rs) | RATE (In Words) | AMOUNT(Rs) |
|---------|---|------|------|-----------|-----------------|------------|
| 1.5     | Providing and fixing bright finished brass 100 mm mortice latch and lock, ISI marked, with six levers and a pair of anodised (anodic coating not less than grade AC 10 as per IS: 1868) aluminium lever handles of approved quality with necessary screws etc. complete.  | 8.00 | Each |           |                 |            |
| 2       | ALUMINIUM WORKS   |      |      |           |                 |            |
| 2.1     | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately): |      | kg   |           |                 |            |
| 2.1.1   | For fixed portion   |      |      |           |                 |            |
| 2.1.1.1 | Powder coated aluminium (minimum thickness of powder coating 50 micron)   |      |      |           |                 |            |
| 2.2.1   | For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)  Powder coated aluminium (minimum thickness of powder coating 50 micron)  |      | kg   |           |                 |            |

| ITEM No | SUB-HEADS AND ITEM OF WORK                                     | QTY    | UNIT | RATE (Rs) | RATE (In Words) | AMOUNT(Rs) |
|---------|--|--------|------|-----------|-----------------|------------|
| 2.3     | Providing and fixing 12 mm thick prelaminated particle         | 160.00 | sqm  |           |                 |            |
|         | board flat pressed three layer or graded wood particle         |        |      |           |                 |            |
|         | board conforming to IS: 12823 Grade 1 Type 11, in              |        |      |           |                 |            |
|         | panelling fixed in aluminum doors, windows shutters and        |        |      |           |                 |            |
|         | partition frames with C.P. brass / stainless steel screws etc. |        |      |           |                 |            |
|         | complete as per architectural drawings and directions of       |        |      |           |                 |            |
|         | engineer-in-charge.  |        |      |           |                 |            |
| 2.3.1   | Pre-laminated particle board with decorative lamination on     |        |      |           |                 |            |
|         | one side and balancing lamination on other side                |        |      |           |                 |            |
|         |  |        |      |           |                 |            |
| 2.4     | Providing and fixing glazing in aluminium door, window,        | 80.00  | sqm  |           |                 |            |
|         | ventilator shutters and partitions etc. with EPDM rubber /     |        |      |           |                 |            |
|         | neoprene gasket etc. complete as per the architectural         |        |      |           |                 |            |
|         | drawings and the directions of engineer-in-charge . (Cost      |        |      |           |                 |            |
|         | of aluminium snap beading shall be paid in basic item):        |        |      |           |                 |            |
|         |  |        |      |           |                 |            |
| 2.4.1   | With float glass panes of 5.0 mm thickness                     |        |      |           |                 |            |

SIGNATURE OF CONTRACTOR